

Amendments to the Claims:

Claims 1, 3-5, 10, 13, 15-17 and 22 were pending at the time of the Office Action.

Claims 1, 3, 10, 13, 15, 17, and 22 are hereby amended.

Claims 1, 3-5, 10, 13, 15-17, and 22 remain pending.

1. (Currently Amended) A payload track adapted for use with a payload assembly, comprising:

an elongated support including a first channel member having a first support surface, a second channel member approximately parallel to and spaced apart from the first channel member having a second support surface approximately co-planar with the first support surface, the support surfaces being configured to engage directly or indirectly with a lower surface of a floor panel; and

an engagement member centrally disposed between the two channel members, wherein a first vertical side of the engagement member is attached to a first adjacent portion of the first channel member and a second vertical side of the engagement member is attached to a second adjacent portion of the second channel member, and the engagement member includes an approximately horizontal top engagement surface configured to be coupled to the payload assembly,

wherein the engagement member and the top engagement surface are at least one of flush with and recessed below the lower surface of the floor panel when the support surfaces are engaged with the lower surface, and wherein the top engagement surface has at least one of an engagement slot and an attachment aperture disposed therein.

2. (Canceled)

3. (Currently Amended) The payload track of Claim 1, wherein the top engagement surface has an engagement slot disposed therein, the engagement slot having a plurality of alternating holes and lands and being configured to cooperatively engage the payload assembly.

4. (Previously Presented) The payload track of Claim 1, wherein each of the first and second channel members includes a plurality of longitudinal sides.

5. (Previously Presented) The payload track of Claim 1, wherein each of the first and second channel members has a "C"-shaped section.

Claims 6-9. (Canceled)

10. (Currently Amended) The payload track of Claim 1, wherein the top engagement surface is co-planar with at least one of the lower surface of the floor panel and the support surfaces when the support surfaces are engaged with the lower surface.

Claims 11-12. (Canceled)

13. (Currently Amended) A payload assembly, comprising:

a payload member having at least one rigid support member; and

a floor assembly including at least one floor panel,

an elongated support having a first channel member having a first support surface, a second channel member approximately parallel to and spaced apart from the first channel member having a second support surface approximately co-planar with the first support surface, the support surfaces being engaged with a lower surface of the floor panel, and

an engagement member centrally disposed between the two channel members, wherein a first vertical side of the engagement member is attached to a first adjacent portion of the first channel member and a second vertical side of the engagement member is attached to a second adjacent portion of the second channel member, and the engagement member includes an approximately horizontal top engagement surface coupled to the rigid support member, wherein the engagement member and the top engagement surface are at least one of flush with and recessed below the lower surface of the floor panel, wherein the top engagement surface has at least one of an engagement slot and an attachment aperture disposed therein.

14. (Canceled)

15. (Currently Amended) The payload assembly of Claim 13, wherein the approximately horizontal top engagement surface has an engagement slot disposed therein, the engagement slot having a plurality of alternating holes and lands and being configured to cooperatively engage the payload assembly.

16. (Previously Presented) The payload assembly of Claim 13, wherein each of the first and second channel members includes a plurality of longitudinal sides.

17. (Currently Amended) A payload assembly, comprising:
a payload member having at least one rigid support member; and
a floor assembly including at least one floor panel,

an elongated support having a first channel member having a first support surface, a second channel member approximately parallel to and spaced apart from the first channel member having a second support surface approximately co-planar with the first support surface, the support surfaces being engaged with a lower surface of the floor panel, and

an engagement member centrally disposed between the two channel members, wherein a first vertical side of the engagement member is attached to a first adjacent portion of the first channel member and a second vertical side of the engagement member is attached to a second adjacent portion of the second channel member, and the engagement member includes an approximately horizontal top engagement surface coupled to the rigid support member, wherein the engagement member and the top engagement surface are at least one of flush with and recessed below the lower surface of the floor panel, wherein each of the first and second channel members has a “C”-shaped cross section.

Claims 18 – 21. (Canceled)

22. (Currently Amended) The payload assembly of Claim 13, wherein the top engagement surface is co-planar with at least one of the lower surface of the floor panel and the support surfaces.

Claims 23 - 49. (Canceled)